



Adhesive: Butyl Rubber
Liner 1: Kraft Paper
Liner 2: Blue LDPE
Specifications: N/A

Applications

- Laminate and bond various substrates
- Eliminating air penetration
- Noise and vibration damping
- Waterproofing and weatherproofing

Features

- Aggressive butyl mastic adhesive
- Easy peel release liner

Benefits

- Bonds to smooth or textured surfaces
- Permanent air and water-tight bond
- Compatible with most sealants
- Maintains flexibility even in cold temperatures
- Retains structural integrity even at high temperatures
- Easy to apply

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	20.0 mils	0.508 mm	ASTM D-1000
Adhesion to Steel	281 oz/in	30.74 N/cm	ASTM D903
Adhesion to Plywood	140 oz/in	15.32 N/cm	ASTM D903
Adhesion to OSB	236 oz/in	25.82 N/cm	ASTM D903
Adhesion to Vinyl	236 oz/in	25.82 N/cm	ASTM D903
Adhesion to Felt	150 oz/in	16.41 N/cm	ASTM D903
Adhesion to Unprimed Brick	150 oz/in	16.41 N/cm	ASTM D903
Adhesion to Housewrap	222 oz/in	24.29 N/cm	ASTM D903
Application Temperature	30 to 180 °F	-1 to 82 °C	
Operating Temperature	-30 to 200 °F	-34 to 93 °C	

Recommended Storage Conditions: 60-80 °F at 40-60% RH

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.