

## Low VOC Premium Spray Adhesive

<b>Product Size:</b>	14 oz Net Wt; 19.6 FL OZ
<b>Spray Pattern:</b>	Lace/Web
<b>Color:</b>	Light Amber
<b>% Solids:</b>	24% Premium Resins
<b>Operating Temp:</b>	-10 to 180 °F (-23 to 82 °C)
<b>Bonding Time:</b>	1 minute to one hour
<b>Evaporation Rate:</b>	20-30 seconds
<b>Coverage Area:</b>	Varies
<b>VOC Content:</b>	<55% by weight

### Applications

- Bonding carpets
- Securing insulation/liner materials to duct work
- Securing labels
- Suitable for permanent or temporary bonds
- Bonding fabric, insulation, plastic films, felt, rubber leather, cork, paper, cardboard, metal, wood
- Excellent for laminating foam materials to a variety of substrates

### Features

- Rubber Based
- Low VOC Content
- Wide Finger Pad Nozzle

### Benefits

- Fast skin, fast grab, low soak-in
- Performs over a wide temperature range
- Good UV, moisture, and oxidation resistance
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®
- Provides increased comfort over extended use

### Application Instructions

- Shake well before applying. Spray an even coat from a distance of 6-8 inches.
- For permanent bonds, spray both surfaces. Allow 1-2 minutes for tack to develop. Apply firm pressure.
- For temporary bonds, apply a light, even coat to one surface; allow tack to develop. Apply firm pressure.
- When finished spraying, turn can upside down and spray for 2 seconds to prevent nozzle from clogging.

**Caution: Extremely Flammable. Please review all safety instructions on the product package prior to use.**

Recommended Storage Conditions: 60-80 °F at 40-60% RH  
Standard Shelf Life (at 25 °C): 24 months from date of manufacture.

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.