


Multi-Purpose PE Tape



Backing: Polyethylene Film

Adhesive: Rubber

Liner: N/A

Colors: Orange, Black

Specifications: N/A

Standard Sizes: 48mm x 55m, 72mm x 55m

Applications

- Stucco and plaster masking
- General purpose outdoor masking
- Bundling, wrapping, and repairs
- General purpose abatement applications such as hanging and patching PE sheeting, securing waste disposal bags, and more

Features

- Polyethylene Film Backing
- Natural Rubber Based Adhesive

Benefits

- Conformable and flexible
- Excellent durability and solvent resistance
- Withstands outdoor exposure and moisture
- High tack for a secure bond
- Repositionable and clean removal - no residue

Typical Test Values

| | Standard UOM | Metric UOM | Test Method |
|------------------------------|--------------|------------|-------------|
| Total Thickness | 7.5 mils | 0.191 mm | ASTM D-1000 |
| Adhesion to Steel | 50 oz/in | 5.47 N/cm | PSTC-101 |
| Adhesion to Backing | 25 oz/in | 2.74 N/cm | PSTC-101 |
| Tensile Strength | 25 lb/in | 43.78 N/cm | ASTM D-1000 |
| Operating Temperature | 40 to 180 °F | 4 to 82 °C | |
| Elongation | 70% | | |

Recommended Storage Conditions: 60-80 °F at 40-60% RH
 Standard Shelf Life (at 25 °C): 24 months from date of manufacture.

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.