


Removable Clean Room Tape



Backing:	LDPE Film
Adhesive:	Acrylic (A105)
Liner:	N/A
Colors:	Blue, White, Tinted Orange, Clear
Specifications:	N/A
Size Options:	Incremental widths 1/4" - 54" x 108ft

Applications

- Sealing clean room containers
- Color coding, product and packaging identification
- Splicing plastic film materials
- Surface and label overlaminates

Features

- LDPE Film
- Acrylic Adhesive
- Plastic Core

Benefits

- Excellent conformability
- Abrasion and moisture resistant
- Solvent resistant
- Low in halogens and leachable chlorides
- Removes cleanly - will not leave residue
- Reduces contamination risk
- Clean and fiber free, recyclable

Typical Test Values

	Standard UOM		Metric UOM		Test Method
Total Thickness	5.5	mils	0.140	mm	PSTC-133
Substrate Thickness	4.5	mils	0.114	mm	PSTC-133
Adhesion to Steel	25	oz/in	2.74	N/cm	ASTM D-3330
Tensile Strength	11	lb/in	19.26	N/cm	ASTM D-3759
Elongation	550%				
Application Temperature	50 to 120 °F		10 to 49 °C		
Operating Temperature	-40 to 190 °F		-40 to 88 °C		

Recommended Storage Conditions: 40-60% Humidity, 60 - 80 °F
Standard Shelf Life (at 25 °C): 12 months from shipment date

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.