


Premium Nuclear Grade Duct Tape



Backing:	PE Coated Cloth
Adhesive:	Rubber
Liner:	N/A
Colors:	Black, Red, Silver, White
Specifications:	Meets NRC Reg 1.38 & ASME NQA-1; Tested in accordance with UL 723.
Standard Sizes:	48mm x 55m, 96mm x 55m

Applications

- Multiple uses in powerplants and on ships
- Color Coding
- Use with nickel-based alloys and austenitic stainless steel
- Holding dosimeters, securing clothing and gloves, wrapping pipe ends, insulation and duct sealing

Features

- PE-Coated Cloth Backing
- Natural Rubber Based Adhesive

Benefits

- High tensile strength for difficult applications
- Puncture and abrasion resistance
- Crisp, straight tear
- Moisture, solvent, and abrasion resistant
- Aggressive adhesion to all surfaces

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	12.0 mils	0.305 mm	ASTM D-1000
Adhesion to Steel	60 oz/in	6.56 N/cm	PSTC-101
Adhesion to Backing	25 oz/in	2.74 N/cm	PSTC-101
Tensile Strength	30 lb/in	52.54 N/cm	ASTM D-1000
Operating Temperature	40 to 200 °F	4 to 93 °C	
VOC Content	<1 g/L		

Recommended Storage Conditions: 60-80 °F at 40-60% RH
Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.