


## UV-Resistant Heavy-Duty PE Tape



<b>Backing:</b>	Polyethylene Film
<b>Adhesive:</b>	Synthetic Rubber
<b>Liner:</b>	N/A
<b>Colors:</b>	Red, White
<b>Specifications:</b>	N/A
<b>Standard Sizes:</b>	48mm x 55m, 72mm x 55m, 96mm x 55m

### Applications

- Short-term outdoor masking for stucco and paint applications (up to 28 days)
- Protection around window and door frames
- Agricultural bagging
- Seam and patch outdoor poly sheeting and tarps
- Greenhouse repair
- Seam and patch shrink wrap for indoor/outdoor storage of marine, RV, and other equipment
- Bonds well to a variety of construction surfaces including plastic, masonry, vinyl, stucco, and metal
- Temporary outdoor surface protection
- Outdoor wire hold down

### Features

- Polyethylene Film Backing
- Synthetic Rubber Adhesive
- Low VOC, Contains no heavy metals (such as lead and chromium)

### Benefits

- Short-term UV resistance for outdoor uses up to 28 days
- Thicker for added durability and solvent resistance
- Low elongation for consistent surface bond
- Pinked/Serrated edge available for hand tearability
- High tack for good quick stick
- Excellent shear strength
- Repositionable and clean removal from many surfaces
- Environmentally friendly and safe to use.

### Typical Test Values

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness (Colors)</b>	9.0 mils	0.229 mm	ASTM D-1000
<b>Adhesion to Steel</b>	85 oz/in	9.30 N/cm	PSTC-101
<b>Adhesion to Backing</b>	39 oz/in	4.27 N/cm	PSTC-101
<b>Tensile Strength</b>	32 lb/in	56.04 N/cm	ASTM D-1000
<b>Permeance</b>	0.10 US Perms		ASTM D-3833
<b>Application Temperature</b>	30 to 160 °F	-1 to 71 °C	
<b>Operating Temperature</b>	20 to 200 °F	-7 to 93 °C	
<b>Elongation</b>	70%		

Recommended Storage Conditions: 60-80 °F at 40-60% RH

Standard Shelf Life (at 25 °C): 24 months from date of manufacture.

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.