


POLYKEN®

335FT

High Temperature Flue Tape



- Backing: 1.75 mil Aluminum Foil
- Adhesive: Acrylic
- Liner: Kraft Paper
- Colors: Aluminum
- Specifications: Tested in accordance with UL 723
- Standard Sizes: 48mm x 46M, 72mm x 46M

Applications

- Seals seams and closures in high heat flue installations
- Welding applications
- Autoclaving and composite applications
- Suitable for use on high efficiency furnace-certified plastic vent pipes
- Heat shielding

Features

- 1.75 mil Foil Backing
- Extreme Temperature Acrylic Adhesive
- Low VOC Content

Benefits

- Excellent conformability
- Resists UV, MOLD, and MOISTURE
- Specially formulated for high temperature performance
- Withstands very cold and very hot application and operating conditions
- Excellent quick stick for an instant seal
- Low odor
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	3.8 mils	0.097 mm	PSTC-133
Adhesion to Steel	35 oz/in	3.83 N/cm	PSTC-101
Tensile Strength	14 lb/in	24.52 N/cm	PSTC-131
Operating Temperature	-50 to 500 °F	-46 to 260 °C	
Minimum Install Temperature	-5 °F	-20 °C	
Smoke Developed	<50		
Flame Spread	<25		
VOC Content	< 30 g/L		

Recommended Storage Conditions: 60-80 °F at 40-60% RH
Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.



2320 Bowling Green Road | Franklin, KY 42134
1-800-343-7875 Fax 1-800-328-4822
www.vybond.com
4/1/2022