

Abatement, Remediation, and Safety Products

POLYKEN[®]

Nashua[®]
TAPE PRODUCTS
PROFESSIONALS' CHOICE



YBOND

PE Cloth Duct Tapes

Polyken and Nashua have been leading brands for the asbestos abatement and mold remediation industry for decades. With an assortment of high performance polyethylene-coated cloth duct tapes with premium natural rubber adhesive, Polyken and Nashua are the trusted and reliable choice for:

- Hanging, sealing, and seaming poly sheeting
- Creating containment areas
- Sealing waste disposal bags
- Sealing gloves, boots, and safety garments
- Color coding
- Bundling, sealing, and repairs



Nashua 307 7 mil Utility Grade



**HIGH ADHESION RUBBER ADHESIVE
CRISP, STRAIGHT TEAR BY HAND
RESISTS TWISTING AND CURLING**

Backing/Adhesive	PE Cloth / Natural Rubber	
Thickness	7.0 mil	0.178 mm
Adh to Steel	65 oz/in	7.11 N/cm
Tensile	22 lb/in	38.53 N/cm
Operating Temp	40 - 200 °F	4 - 93 °C
Colors	Silver, Black	
Std Size	48mm, 72mm x 55M	

Nashua 308 8 mil Utility Grade



**BONDS TO SMOOTH OR ROUGH SURFACES
CRISP, STRAIGHT TEAR BY HAND
RESISTS TWISTING AND CURLING**

Backing/Adhesive	PE Cloth / Natural Rubber	
Thickness	8.0 mil	0.203 mm
Adh to Steel	55 oz/in	6.02 N/cm
Tensile	22 lb/in	38.53 N/cm
Operating Temp	40 - 200 °F	4 - 93 °C
Colors	Silver, Black	
Std Size	48mm, 72mm x 55M	


Nashua 2280 9 mil Multi-Purpose Grade



**STRONG ADHESION TO ROUGH SURFACES
EXCELLENT TENSILE AND TEARABILITY
GOOD SHEAR STRENGTH**

Backing/Adhesive	PE Cloth / Natural Rubber	
Thickness	9.0 mil	0.229 mm
Adh to Steel	70 oz/in	7.66 N/cm
Tensile	24 lb/in	42.03 N/cm
Operating Temp	40 - 200 °F	4 - 93 °C
Colors	Silver, Black, White, Blue, Red, Brown, Burgundy, Green, OD, Tan, Yellow	
Std Size	48mm, 72mm x 55M	

Nashua 300 10 mil Multi-Purpose Grade



**GOOD ADHESION AND SHEAR STRENGTH
EXCELLENT CONFORMABILITY
BONDS TO ROUGH OR SMOOTH SURFACES**

Backing/Adhesive	PE Cloth / Natural Rubber	
Thickness	10.0 mil	0.254 mm
Adh to Steel	75 oz/in	8.21 N/cm
Tensile	24 lb/in	42.03 N/cm
Operating Temp	40 - 200 °F	4 - 93 °C
Colors	Silver, Black	
Std Size	48mm, 72mm x 55M	

Nashua 398 11 mil Professional Grade



**AGGRESSIVE BOND TO SURFACES
EXCELLENT TENSILE AND TEARABILITY
HIGH SHEAR STRENGTH**

Backing/Adhesive	PE Cloth / Natural Rubber	
Thickness	11.0 mil	0.279 mm
Adh to Steel	80 oz/in	8.75 N/cm
Tensile	26 lb/in	45.53 N/cm
Operating Temp	40 - 200 °F	4 - 93 °C
Colors	Silver, Black, White, Blue, Red, Brown, Green, OD, Tan, Yellow	
Std Size	48mm, 72mm x 55M	

Nashua 357 13 mil Premium Grade



**EXCELLENT ADHESION AND SHEAR
PUNCTURE AND ABRASION RESISTANT
EXCELLENT MOISTURE RESISTANCE**

Backing/Adhesive	PE Cloth / Natural Rubber	
Thickness	13.0 mil	0.330 mm
Adh to Steel	95 oz/in	10.39 N/cm
Tensile	50 lb/in	87.56 N/cm
Operating Temp	40 - 200 °F	4 - 93 °C
Colors	Silver, Black, Olive Drab, Red, White, Printed Silver	
Std Size	48mm, 72mm x 55M	

Nashua 850UV
8.5 mil UV Resistant



UV RESISTANT (<14 DAYS)
GOOD ADHESION AND SHEAR STRENGTH
WITHSTANDS OUTDOOR CONDITIONS

Backing/Adhesive	PE Cloth / Natural Rubber	
Thickness	8.5 mil	0.216 mm
Adh to Steel	62 oz/in	6.78 N/cm
Tensile	21 lb/in	36.78 N/cm
Operating Temp	40 - 200 °F	4 - 93 °C
Colors	Red, White	
Std Size	48mm, 72mm x 55M	



Polyken 203
9 mil Multi-Purpose Grade



EXCELLENT ADHESION AND TACK
BALANCED TEAR AND TENSILE
GOOD REMOVABILITY FROM SURFACES

Backing/Adhesive	PE Cloth / Natural Rubber	
Thickness	9.0 mil	0.229 mm
Adh to Steel	85 oz/in	9.30 N/cm
Tensile	25 lb/in	43.78 N/cm
Operating Temp	40 - 200 °F	4 - 93 °C
Colors	Black, Silver, White, Blue, Green, Olive Drab, Yellow	
Std Size	48mm, 72mm x 55M	

Polyken 244
10 mil Abatement



EXCELLENT BOND TO POLY SHEETING
CRISP, STRAIGHT TEAR
RESISTS TWISTING AND CURLING

Backing/Adhesive	PE Cloth / Natural Rubber	
Thickness	10.0 mil	0.254 mm
Adh to Steel	80 oz/in	8.75 N/cm
Tensile	24 lb/in	42.03 N/cm
Operating Temp	40 - 200 °F	4 - 93 °C
Colors	Teal	
Std Size	48mm, 72mm x 55M	


Polyken 223
10 mil Multi-Purpose Grade



EXCELLENT ADHESION AND TACK
BALANCED TEAR AND TENSILE
GOOD REMOVABILITY FROM SURFACES

Backing/Adhesive	PE Cloth / Natural Rubber	
Thickness	10.0 mil	0.254 mm
Adh to Steel	90 oz/in	9.85 N/cm
Tensile	25 lb/in	43.78 N/cm
Operating Temp	40 - 200 °F	4 - 93 °C
Colors	Black, Silver, White, Blue, Green, Olive Drab, Yellow	
Std Size	48mm, 72mm x 55M	

Polyken 253
13 mil Premium Grade



EXCEPTIONAL ADHESION AND SHEAR
HIGH TENSILE STRENGTH
CLEAN, CRISP STRAIGHT TEAR

Backing/Adhesive	PE Cloth / Natural Rubber	
Thickness	13.0 mil	0.330 mm
Adh to Steel	95 oz/in	10.39 N/cm
Tensile	50 lb/in	87.56 N/cm
Operating Temp	40 - 200 °F	4 - 93 °C
Colors	Silver, Black	
Std Size	48mm, 72mm x 55M	

Polyken 235FR
12 mil Flame Retardant



FLAME RETARDANT
HIGH TENSILE STRENGTH
RESISTS MOISTURE AND SOLVENTS

Backing/Adhesive	PE Cloth / Natural Rubber	
Thickness	12.0 mil	0.305 mm
Adh to Steel	40 oz/in	4.38 N/cm
Tensile	29 lb/in	50.79 N/cm
Operating Temp	40 - 200 °F	4 - 93 °C
Colors	Silver	
Std Size	48mm, 72mm x 55M	

Polyken 225FR
12 mil Flame Retardant



FLAME RETARDANT - PRINTED
HIGH TENSILE STRENGTH
STRONG BOND TO SURFACES

Backing/Adhesive	PE Cloth / Natural Rubber	
Thickness	12.0 mil	0.305 mm
Adh to Steel	40 oz/in	4.38 N/cm
Tensile	29 lb/in	50.79 N/cm
Operating Temp	40 - 200 °F	4 - 93 °C
Colors	White (Printed)	
Std Size	48mm, 72mm x 55M	

Double-Coated Tapes

With the strength and tearability of duct tape, Polyken and Nashua double-coated cloth tapes are an ideal solution for creating containment areas in abatement, remediation, cleaning, and construction operations. Designed to bond to virtually any smooth or rough surfaces and with clean-removal solutions where needed, trust Polyken and Nashua to provide the right one-step tape solution for your application.



NASHUA CLEANDRAPE® Heavy-Duty Poly Hanging Tape



14-DAY CLEAN REMOVAL*
DUCT TAPE STRENGTH AND DURABILITY
EXCELLENT SHEAR STRENGTH

ONE-STEP, CLEAN REMOVAL POLY HANGING TAPE FOR SHEETING AND TARPS TO CREATE CONTAINMENT AREAS FOR CLEANING, ABATEMENT, AND CONSTRUCTION.

Carrier/Adhesive	Cloth / Natural Rubber	
Thickness	15.0 mil	0.381 mm
Adh to Steel (Air)	25 oz/in	2.74 N/cm
Adh to Steel (Lnr)	40 oz/in	4.38 N/cm
Tensile	63 lb/in	110.33 N/cm
Colors	Blue/Tan	
Std Size	2in x 20Yd	

NASHUA CLEANDRAPE® SHEAR Poly Hanging Tape



CLEAN REMOVAL FROM SURFACES*
EXCEPTIONAL HIGH SHEAR STRENGTH
DIFFERENTIAL BOND FOR ONE-STEP

ONE-STEP, CLEAN REMOVAL POLY HANGING TAPE FOR SHEETING AND TARPS TO CREATE CONTAINMENT AREAS FOR CLEANING, ABATEMENT, AND CONSTRUCTION.

Carrier/Adhesive	Cloth / Synthetic Rubber	
Thickness	6.0 mil	0.152 mm
Adh to Steel (Air)	35 oz/in	3.83 N/cm
Adh to Steel (Lnr)	55 oz/in	6.02 N/cm
Tensile	19 lb/in	33.27 N/cm
Colors	Clear	
Std Size	48mm, 72mm x 18.3M	

POLYKEN 105C 11 mil Multi-Purpose DC Cloth



BONDS TO SMOOTH OR ROUGH SURFACES
CLEAN REMOVAL FROM MANY SURFACES
EASY TO USE RELEASE LINER

TEMPORARY CARPET INSTALLATION FOR CONVENTION AND HOSPITALITY INDUSTRY. HANG AND SEAM POLY SHEETING. MOUNTING USES.

Carrier/Adhesive	Cloth / Natural Rubber	
Thickness	11.0 mil	0.279 mm
Adh to Steel	40 oz/in	4.38 N/cm
Tensile	20 lb/in	35.03 N/cm
Operating Temp	40 - 200 °F	4 - 93 °C
Colors	Natural (LDPE or Paper Liner)	
Std Size	48mm, 72mm x 23M or 33M	

POLYKEN 100D 13 mil Premium DC Cloth



EXCELLENT BOND TO ROUGH MATERIALS
CLEAN REMOVAL FROM MANY SURFACES
EASY TO USE RELEASE LINER

TEMPORARY CARPET INSTALLATION FOR CONVENTION AND HOSPITALITY INDUSTRY. HANG AND SEAM HEAVY POLY SHEETING. MOUNTING USES.

Carrier/Adhesive	Cloth / Natural Rubber	
Thickness	13.0 mil	0.330 mm
Adh to Steel	45 oz/in	4.92 N/cm
Tensile	30 lb/in	54.54 N/cm
Operating Temp	40 - 200 °F	4 - 93 °C
Colors	Natural (LDPE or Paper Liner)	
Std Size	48mm, 72mm x 23M or 33M	



Spray Adhesives

Leveraging Vybond’s expertise in natural rubber adhesive formulation, Nashua offers premium and multi-purpose web/lace spray adhesives used in abatement/remediation, manufacturing and fabrication, insulation, mounting, bonding, and laminating applications across a variety of industries. With exceptional strength and holding power, these products offer both permanent and temporary bonding capability to suit your application.



Nashua 357SA Premium Web Spray Adhesive



**LOW VOC - MEETS SCAQMD STANDARDS
RESISTS UV, MOISTURE, AND OXIDATION
EXCELLENT SHEAR STRENGTH**

**HEAVY-DUTY PERMANENT OR TEMPORARY
BONDS FOR FOILS, METALS, FABRICS,
LEATHER, RUBBER, WOOD, PLASTICS.
SECURES INSULATION MATERIALS.
PRIMES SURFACES.**

Base Adhesive	Rubber	
Color	Water White	
VOC Content	<40% by Weight	
% Solids	24% Premium Resins	
Operating Temp	-10 - 180 °F	-23 - 88 °C
Std Size	20 FL OZ (14 oz Net Wt)	

Nashua 398SA Multi-Purpose Web Spray Adhesive



**LOW VOC - MEETS SCAQMD STANDARDS
PERMANENT OR TEMPORARY BONDS
GOOD SHEAR STRENGTH**

**GENERAL PURPOSE BONDING FOR
FOILS, FABRICS, LEATHER, RUBBER,
WOOD, PLASTICS. SECURES INSULATION
MATERIALS. PRIMES SURFACES.**

Base Adhesive	Rubber	
Color	Water White	
VOC Content	<40% by Weight	
% Solids	23% Resins	
Operating Temp	-10 - 110 °F	-23 - 43 °C
Std Size	17 FL OZ (12 oz Net Wt)	

Did You Know...? Not all duct tapes are “created” equal. The adhesive formulation (natural rubber or synthetic rubber), the backing composition (PE blend and cloth type), and the method in which these materials are put together all play a role in influencing product performance. Depending on these factors, a duct tape will be well-suited for some applications but not others.

In fact, adhesives have three key performance characteristics: Peel, Shear, and Tack. An adhesive can be designed to offer high values in one or two of these, but never all three. Call upon the experts at Vybond to discuss the needs of your demanding application to determine which product will work best for your needs.

PEEL (Adhesion):

The force required to pull a strip of tape from a surface at a specified angle and speed.

SHEAR (Holding Strength):

The bond strength of a tape when stressed at a zero degree angle.

TACK (Quick Stick):

The ability of an adhesive to form a measurably strong bond immediately after low-pressure surface contact.



Film Tapes

Polyken Tapes is among the pioneers in the polyethylene film tape markets. With expertise in adhesive formulation, coating, and calendaring, we offer a breadth of tapes suited for both temporary and permanent uses, clean removal, UV exposure, extreme temperatures, abrasion, solvent, and moisture resistance, and more.



Polyken 757

7 mil Multi-Purpose PE Film



EXCELLENT TACK AND SHEAR STRENGTH
REPOSITIONABLE, CLEAN REMOVAL*
DURABLE AND SOLVENT RESISTANT
PINKED OR STRAIGHT EDGES

HANG, SEAM, SEAL, AND PATCH POLY SHEETING. BUNDLING AND SEALING WASTE DISPOSAL BAGS. SEALING SAFETY CLOTHING. SHORT TERM MASKING AND SURFACE PROTECTION. COLOR CODING.

Backing/Adhesive	PE Film / Synthetic Rubber	
Thickness	7.0 mil	0.178 mm
Adh to Steel	75 oz/in	8.21 N/cm
Tensile	25 lb/in	43.78 N/cm
Operating Temp	20 - 200 °F	-7 - 93 °C
Colors	Red, White, Clear, Black, Green, Teal, Blue, Orange, Silver	
Std Size	48mm, 72mm x 55M	

Polyken 759

9 mil Heavy-Duty PE Film



THICK BACKING FOR ADDED DURABILITY
HIGH TACK, GOOD QUICK STICK
SUPERIOR BOND TO ROUGH SURFACES
PINKED OR STRAIGHT EDGES

TEMPORARY ENCLOSURES OR CONTAINMENT AREAS. HEAVY-DUTY BUNDLING, SPLICING, AND REPAIRS.

Backing/Adhesive	PE Film / Synthetic Rubber	
Thickness	9.0 mil	0.229 mm
Adh to Steel	85 oz/in	9.30 N/cm
Tensile	30 lb/in	52.54 N/cm
Operating Temp	20 - 200 °F	-7 - 93 °C
Colors	Red, White, Clear	
Std Size	48mm, 96mm x 55M	

Polyken 824 Red Baron

7 mil Multi-Purpose PE Film



HIGH TACK ADHESIVE
REPOSITIONABLE, CLEAN REMOVAL*
CONFORMABLE AND FLEXIBLE
PINKED OR STRAIGHT EDGES

STUCCO AND PLASTER MASKING. GENERAL PURPOSE OUTDOOR MASKING. BUNDLING, WRAPPING, AND REPAIRS. ABATEMENT.

Backing/Adhesive	PE Film / Natural Rubber	
Thickness	7.0 mil	0.178 mm
Adh to Steel	45 oz/in	4.92 N/cm
Tensile	20 lb/in	35.03 N/cm
Operating Temp	40 - 200 °F	4 - 93 °C
Colors	Red, White	
Std Size	48mm, 72mm x 55M	

Polyken 827

8 mil Premium PE Film




HIGH TACK FOR A SECURE BOND
REPOSITIONABLE, CLEAN REMOVAL*
CONFORMABLE AND FLEXIBLE
PINKED OR STRAIGHT EDGES

STUCCO AND PLASTER MASKING. OUTDOOR MASKING. SURFACE PROTECTION. VAPOR BARRIER SEALING.

Backing/Adhesive	PE Film / Natural Rubber	
Thickness	8.0 mil	0.203 mm
Adh to Steel	60 oz/in	6.56 N/cm
Tensile	21 lb/in	36.78 N/cm
Operating Temp	40 - 200 °F	4 - 93 °C
Colors	Clear, Black, Red, White	
Std Size	48mm, 72mm x 55M	

Polyken 767UV

7 mil Multi-Purpose UV PE Film




CLEAN REMOVAL UP TO 28 DAYS*
DURABLE AND SOLVENT RESISTANT
EXCELLENT SHEAR STRENGTH
PINKED OR STRAIGHT EDGES

OUTDOOR MASKING FOR STUCCO AND PAINT APPLICATION. WINDOW/DOOR FRAME AND OTHER OUTDOOR SURFACE PROTECTION.

Backing/Adhesive	PE Film / Synthetic Rubber	
Thickness	7.0 mil	0.178 mm
Adh to Steel	75 oz/in	8.21 N/cm
Tensile	25 lb/in	43.78 N/cm
Operating Temp	20 - 200 °F	-7 - 93 °C
Colors	Red, White	
Std Size	48mm, 96mm x 55M	

Polyken 769UV

9 mil Heavy-Duty UV PE Film



CLEAN REMOVAL UP TO 28 DAYS*
THICK, DURABLE, AND SOLVENT RESISTANT
EXCELLENT SHEAR STRENGTH
PINKED OR STRAIGHT EDGES

OUTDOOR MASKING FOR STUCCO AND PAINT. SEAMING HEAVY-DUTY POLY SHEETING. WINDOW/DOOR FRAME AND OTHER OUTDOOR SURFACE PROTECTION.

Backing/Adhesive	PE Film / Synthetic Rubber	
Thickness	9.0 mil	0.229 mm
Adh to Steel	85 oz/in	9.30 N/cm
Tensile	32 lb/in	56.04 N/cm
Operating Temp	20 - 200 °F	-7 - 93 °C
Colors	Red, White	
Std Size	48mm, 96mm x 55M	

Paper Masking Tapes

Nashua paper masking tapes help you get preparation and surface protection applications done right the first time for abatement, remediation, cleaning, and paint operations. From our utility grade crepe masking tape to our premium 14-day painter's masking tape, we have the product for your application.



Nashua 140B Premium 14-Day Painter's Masking



UV, MOISTURE, SOLVENT RESISTANT
OFFERS UP TO 14 DAYS CLEAN REMOVAL
ADHERES TO A VARIETY OF SURFACES

INDOOR/OUTDOOR MASKING USES.
SURFACE PROTECTION. SECURING POLY
SHEETING FOR PROFESSIONAL
PAINTING AND CLEANING.

Backing/Adhesive	Crepe / Rubber	
Thickness	5.3 mils	0.134 mm
Adh to Steel	25 oz/in	2.74 N/cm
Tensile	24 lb/in	42.03 N/cm
Operating Temp	40 - 130 °F	4 - 54 °C
Colors	Blue	
Std Size	24mm, 36mm, 48mm x 55M	

Nashua MT300 Multi-Purpose Masking



CONFORMABLE, MOISTURE RESISTANT
OFFERS 24-72 HOURS CLEAN REMOVAL
ADHERES TO A VARIETY OF SURFACES

INDOOR/OUTDOOR HOUSEHOLD
AND NON-CRITICAL PAINT MASKING,
BUNDLING, LABELING, AND PACKAGING.

Backing/Adhesive	Crepe / Rubber	
Thickness	6.0 mils	0.152 mm
Adh to Steel	38 oz/in	4.16 N/cm
Tensile	22 lb/in	38.53 N/cm
Operating Temp	40 - 180 °F	4 - 82 °C
Colors	Natural	
Std Size	36mm, 48mm, 72mm x 55M	

Nashua MT100 Utility Masking



CONFORMABLE, MOISTURE RESISTANT
OFFERS UP TO 24 HOURS CLEAN REMOVAL
ADHERES TO A VARIETY OF SURFACES

GENERAL HOUSEHOLD AND OFFICE
MASKING USES. BUNDLING, LABELING,
AND PACKAGING.

Backing/Adhesive	Crepe / Rubber	
Thickness	4.8 mils	0.122 mm
Adh to Steel	42 oz/in	4.59 N/cm
Tensile	16 lb/in	28.02 N/cm
Operating Temp	40 - 150 °F	4 - 65 °C
Colors	Natural	
Std Size	18mm, 24mm, 36mm, 48mm x 55M	





Polyken® and Nashua®, are registered trademarks of Vybond Group, Inc. or one of its affiliates.