



- Backing:** Customer-Supplied LLDPE Film
- Adhesive:** Acrylic
- Liner:** 70# Coated Kraft Paper
- Std Sizes:** 4in x 160ft, 12in x 50ft

Applications

- Patching and seaming of gas barrier films

Features

- Acrylic Adhesive
- Kraft Paper Release Liner

Benefits

- Aggressive bond to gas barrier films
- Excellent all temperature performance
- Excellent long-term stability
- Smooth clean release - easy to use
- Die cuttable

Typical Test Values

	Standard UOM		Metric UOM		Test Method
Total Thickness	9.0	mils	0.229	mm	PSTC-133
Substrate Thickness	7.0	mils	0.178	mm	PSTC-133
Adhesion to Steel	77	oz/in	8.42	N/cm	ASTM D-3330
Tensile Strength	30	lb/in	52.54	N/cm	ASTM D-3759
Elongation	750%				
Application Temperature	50 to 120 °F		10 to 49° C		
Operating Temperature	-40 to 190 °F		-40 to 88 °C		

Recommended Storage Conditions: 40-60% Humidity, 60 - 80 °F

Standard Shelf Life (at 25 °C): 12 months from shipment date

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.