


M-Tak® Differential Double-Coated Tape



Carrier: Polyester Film

Adhesive: Differential Synthetic Rubber (HM809)

Liner: 54# SC Kraft with Finger-Lift Edge™

Product Constructions Available

Number	TW	TL	AW
4747	1.75"	1800ft	1.5"

Applications

- Labels and business forms
- Signs, posters, and advertisements
- Mailer and envelope sealing
- POP Tags

Features

- Synthetic Rubber Adhesive
- PET Film Carrier
- Finger-lift Edge Liner

Benefits

- High adhesion for secure, permanent bond
- Good cold-temperature performance
- Provides support and structure for added stability
- Conformable
- Easy to start, easy to use
- Liner removes clean and smooth

Typical Test Values

	Standard UOM		Metric UOM		Test Method
Tape Thickness (w/o liner)	7.7	mils	0.196	mm	ASTM D-1000
Liner Thickness	3.2	mils	0.081	mm	ASTM D-1000
Air-Side Adhesive Thickness	2.7	mils	0.069	mm	ASTM D-1000
Liner Side Adhesive Thickness	4.5	mils	0.114	mm	ASTM D-1000
Overall Thickness	10.9	mils	0.277	mm	ASTM D-1000
Adhesion to Steel (Air Side)	50	oz/in	5.47	N/cm	ASTM D-3330
Adhesion to Steel (Liner Side)	105	oz/in	11.49	N/cm	ASTM D-3330
Application Temperature Range	30 to 140 °F		4 to 40 °C		
Operating Temperature Range	-30 to 165 °F		-29 to 71 °C		

Recommended Storage Conditions: 60-80 °F at 40-60% RH
Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.