


Utility Extreme Weather Foil Tape



- Backing:** 1.5 mil Aluminum Foil
- Adhesive:** Acrylic
- Liner:** Polycoated Natural Kraft Paper
- Colors:** Aluminum
- Specifications:** Tested in accordance with UL 723
- Standard Sizes:** 48mm x 46M, 72mm x 46M

Applications

- Taping joints and seams in duct work for A/C, heating, and ventilation systems
- Insulation seaming and patching
- Sealing insulation and repairing in cooler/refrigeration applications
- General purpose industrial and automotive uses
- Aircraft sealing and masking
- Window mask to protect aircraft canopies, windshields and passenger window surfaces from crazing or hazing during paint stripping

Features

- 1.5 mil Aluminum Foil Backing
- High Performance Acrylic Adhesive
- Low VOC Content

Benefits

- Conformable to fit corners and joints
- UV, moisture, and mold resistant
- Low odor
- High tack, aggressive bond to surfaces
- Excellent performance in extreme cold or heat
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	3.0 mils	0.076 mm	ASTM D-1000
Foil Thickness	1.5 mils	0.038 mm	ASTM D-1000
Adhesion to Steel	45 oz/in	4.92 N/cm	PSTC-101
Tensile Strength	11 lb/in	19.26 N/cm	ASTM D-1000
Operating Temperature	-35 to 260 °F	-37 to 127 °C	
Minimum Application Temp	-5 °F	-20 °C	
Smoke Developed	<50		
Flame Spread	<25		
VOC Content	<30 g/L		

Recommended Storage Conditions: 60-80 °F at 40-60% RH
 Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.