


## Utility Preservation & Sealing Tape



<b>Backing:</b>	LDPE Film
<b>Adhesive:</b>	Rubber (R400)
<b>Liner:</b>	N/A
<b>Colors:</b>	Clear
<b>Specifications:</b>	N/A
<b>Size Options:</b>	Incremental widths 1/4" - 46" x 108ft

### Applications

- Sealing, patching, and splicing polyethylene sheeting or shrink film used for construction, mobile homes, outdoor equipment, and material storage
- General purpose patch and repair
- Used in suncatcher production to secure frames during epoxy painting - allows for a clear, defect-free surface

### Features

- LDPE Film
- Rubber Adhesive

### Benefits

- Conformable for irregular surfaces
- Abrasion resistant
- Transparent for less visible repairs
- Moisture, solvent, and chemical resistant
- Good quick stick
- Sticks aggressively to most surfaces
- Smooth unwind

### Typical Test Values

	Standard UOM		Metric UOM		Test Method
<b>Total Thickness</b>	8.0	mils	0.203	mm	PSTC-133
<b>Substrate Thickness</b>	7.0	mils	0.178	mm	PSTC-133
<b>Adhesion to Steel</b>	25	oz/in	2.74	N/cm	ASTM D-3330
<b>Tensile Strength</b>	15	lb/in	26.27	N/cm	ASTM D-3759
<b>Elongation</b>	450%				
<b>Application Temperature</b>	50 to 120 °F		10 to 49 °C		
<b>Operating Temperature</b>	50 to 190 °F		10 to 88 °C		

Recommended Storage Conditions: 40-60% Humidity, 60 - 80 °F  
Standard Shelf Life (at 25 °C): 12 months from shipment date

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.