


General Purpose Electrical Tape



Backing

Adhesive

- Backing:** PVC Film
Adhesive: Rubber
Liner: N/A
Colors: Blue, Green, Red, White, Yellow
Specifications: UL 510 Classified
Standard Sizes: 3/4" x 66Ft

Applications

- Wire splicing
- Wire insulation
- Spiral wrapping electrical wire and harnesses
- Color coding

Features

- PVC Backing
- Rubber Adhesive
- UL 510 Classified

Benefits

- Stretchy and conformable for wrapping wires
- Durable
- Conformable
- Provides a strong long-term bond
- No flagging or lifting
- Meets requirements for most electrical applications

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	7.0 mils	0.178 mm	ASTM D-1000
Adhesion to Steel	25 oz/in	2.74 N/cm	PSTC-101
Tensile Strength	20 lb/in	35.03 N/cm	ASTM D-1000
Elongation	200%		
Dielectric Strength	9500V		
Operating Temperature	40 - 180 °F	4 - 82 °C	

Recommended Storage Conditions: 60-80 °F at 40-60% RH
Standard Shelf Life (at 25 °C): 5 years from date of manufacture.

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.