


## Permanent/Removable Double-Coated Tape



**Liner:** 74# Polycoated Kraft

**Liner Side Adhesive:** Acrylic (I628)

**Backing/Carrier:** 0.5 mil PET Film

**Air Side Adhesive:** Acrylic (I632)

### Applications

- Bonding and laminating to foams, fabrics, and non-wovens where clean removal is required
- General purpose bonding uses

### Features

- Air-Side Acrylic Adhesive
- Polyester Film Carrier
- Liner-Side Acrylic Adhesive
- 74# Kraft Liner

### Benefits

- High tack and shear
- Moderate peel
- Bonds to a variety of substrates
- Support for aid in processing and application
- Conformable
- Good bond to surfaces
- Clean removal from many substrates
- Repositionable
- Good lay-flat; moisture resistant

### Typical Test Values

	Standard UOM	Metric UOM	Test Method
<b>Overall Thickness (w/liner)</b>	8.2 mils	0.208 mm	PSTC 133
<b>Air-Side Adhesive Thickness</b>	1.2 mils	0.030 mm	PSTC 133
<b>Carrier Thickness</b>	0.5 mils	0.013 mm	PSTC 133
<b>Liner Side Adhesive Thickness</b>	1.0 mils	0.025 mm	PSTC 133
<b>Liner Thickness</b>	5.5 mils	0.140 mm	PSTC 133
<b>Adhesion to Steel (Air Side)</b>	40 oz/in	4.38 N/cm	PSTC 101 Mod - 1 mil PET
<b>Adhesion to Steel (Liner Side)</b>	32 oz/in	3.50 N/cm	PSTC 101 Mod - 1 mil PET
<b>Shear Strength</b>	>7 Days		PSTC 107 Mod
<b>Laminating Temperature</b>	68 to 100 °F	20 to 38 °C	
<b>Service Temperature</b>	-30 to 220 °F	-34 to 104 °C	

Recommended Storage Conditions: 40-60% Humidity, 60 °F - 80 °F

Standard Shelf Life: 24 months from date of shipment

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.