


## Premium UL 181A-P & 181B-FX Listed Foil Tape



- Backing:** Printed 2.1 mil Aluminum Foil
- Adhesive:** Cold weather Acrylic
- Liner:** Polycoated Natural Kraft Liner
- Colors:** Aluminum
- Specifications:** UL 181A-P & UL 181B-FX Listed
- Standard Sizes:** 2.5" x 60Yd, 72mm x 55m

### Applications

- Permanently seals seams in fiberglass duct board and flexible ducts for HVAC systems
- Suitable for use on rigid sheet metal ducts
- Durable seal for dryer ventilation

### Features

- Aggressive cold weather acrylic adhesive
- Kraft Release Liner
- UL 181A-P & 181B-FX Listed
- Low VOC Content

### Benefits

- Superior performance in all climate conditions
- Low odor
- Mold and mildew resistant
- Reduced environmental impact
- Meets code requirements and can contribute toward requirements for EA Credit 1 (Optimize Energy Performance) under LEED®
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

### Typical Test Values

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness w/o Liner</b>	4.8 mils	0.122 mm	ASTM D-1000
<b>Foil Thickness</b>	2.1 mils	0.053 mm	ASTM D-1000
<b>Adhesion to Steel</b>	68 oz/in	7.44 N/cm	PSTC-101
<b>Adhesion to Backing</b>	60 oz/in	6.56 N/cm	PSTC-101
<b>Tensile Strength</b>	28 lb/in	49.04 N/cm	ASTM D-1000
<b>Application Temperature</b>	-10 to 200 °F	-23 to 93 °C	
<b>Operating Temperature</b>	-25 to 325 °F	-32 to 163 °C	
<b>Flame Spread</b>	3		
<b>Smoke Developed</b>	0		
<b>VOC Content</b>	<1 g/L		

Recommended Storage Conditions: 60-80 °F at 40-60% RH  
 Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.