

POLYKEN®

510W

Thread Seal Tape



Backing: PTFE Film

Adhesive: N/A

Liner: N/A

Colors: White

Standard Sizes: 0.5" x 520", 0.75" x 520", 1" x 520"

Applications

- Self-lubricating tape for wrapping threads : pipe connections making them easy to assemble and disassemble.
- Extends fatigue life of sealed connections and eliminates system contamination common with messy liquid and paste sealants.

Features

- PTFE Film

Benefits

- Self-lubricates
- Easy to use
- Increases ease of assembly
- Unlimited shelf life

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	3.5 mils	0.089 mm	ASTM D-1000
Pressure Rating	<10,000 psi		
Temperature Range	-450 to 500 °F	-267 to 260 °C	

Recommended Storage Conditions: 60-80 °F at 40-60% RH
Standard Shelf Life (at 25 °C): Unlimited

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To Berry Global's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.



2320 Bowling Green Road | Franklin, KY 42134
1-800-343-7875 Fax 1-800-328-4822
www.vybond.com
5/16/2023