


## Professional Grade Duct Tape (Metallic)



**Backing:** Metallized PE Coated Cloth  
**Adhesive:** Rubber  
**Liner:** N/A  
**Colors:** Metallic

**Standard Sizes:** 48mm x 55m, 72mm x 55m

### Applications

- Duct sealing for flexible and rigid duct where UL Listing is not required
- Sealing and patching insulation materials
- Patch, bundle, repair, and mending applications throughout the HVAC jobsite

### Features

### Benefits

- |                                                                                        |                                                                                                                                                                                                                                                                                                    |
|----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• Metallized PE-Coated Cloth Backing</li> </ul> | <ul style="list-style-type: none"> <li>• Conformable and aesthetically similar to most HVAC duct and insulation systems</li> <li>• Improved strength and durability for severe use with no delamination</li> <li>• Clean, straight tear for speedy installs and professional appearance</li> </ul> |
| <ul style="list-style-type: none"> <li>• Reformulated Rubber Adhesive</li> </ul>       | <ul style="list-style-type: none"> <li>• Aggressive adhesion to metal, fiberglass, and flex duct systems</li> <li>• Permanent bond to reflective/bubble insulation</li> <li>• Improved cold weather performance</li> </ul>                                                                         |
| <ul style="list-style-type: none"> <li>• Low VOC Content</li> </ul>                    | <ul style="list-style-type: none"> <li>• Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®</li> </ul>                                                                                                                                                            |

### Typical Test Value

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	11.0 mils	0.279 mm	ASTM D-1000
<b>Adhesion to Steel</b>	85 oz/in	9.30 N/cm	PSTC-101
<b>Tensile Strength</b>	50 lb/in	87.56 N/cm	ASTM D-1000
<b>Elongation</b>	22%		ASTM D-1000
<b>Operating Temperature</b>	30 to 200 °F	-1 to 93 °C	
<b>VOC Content</b>	<1 g/L		

Recommended Storage Conditions: 60-80 °F at 40-60% RH  
 Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.