


Premium 14-Day Blue Masking Tape



Backing
Adhesive

Backing: Saturated Crepe Paper

Adhesive: Synthetic Rubber

Liner: N/A

Colors: Blue

Standard Sizes: 24mm x 55M, 48mm x 55M, 72mm x 55m

Applications

- Painter's grade masking tape for a variety of surfaces
- Interior or exterior uses
- Clean removal masking for metal, glass, wood, vinyl and plastics

Features

- Crepe Paper Backing
- Rubber Adhesive
- UV Resistant

Benefits

- Hand Tearable
- Conformable
- Holds up to most paints and other moisture
- Good bond to most surfaces
- Clean removal for up to 14 days
- Suitable for sunlight exposure

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	5.1 mils	0.130 mm	ASTM D-1000
Adhesion to Steel	33 oz/in	3.61 N/cm	PSTC-101
Tensile Strength	23 lb/in	40.28 N/cm	ASTM D-1000
Elongation	10%		
Temperature Resistance	50 to 200 °F	10 to 93 °C	

Not recommended for laquer, varnish or urethane finishes. Do not use on wallpaper, unpainted wallboard, wood floors or poorly bonded finishes.

Recommended Storage Conditions: 60-80 °F at 40-60% RH

Standard Shelf Life (at 25 °C): 12 months from date of manufacture.

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.

2320 Bowling Green Road | Franklin, KY 42134

1-800-343-7875 Fax 1-800-328-4822

www.vybond.com

3/25/26