


## Heavy-Duty Surface Protection Tape



**Backing:** Interior-Grade Aromatic Polyurethane

**Adhesive:** Urethane (U510)

**Liner:** 94# Coated Kraft Paper

**Colors:** Transparent

**Specifications:** N/A

**Size Options:** Incremental sizes 1/4" - 48" x 108Ft

### Applications

- Heavy-duty, short- or long-term surface protection
- Anti-squeak, vibration, and sound damping for marine and automotive OEM
- Protective film for shot peening in metal cleaning operations
- Surface protection for air foil and ground effects panels on racing cars and trucks

### Features

- Polyurethane Film Backing
- Urethane-based Adhesive
- Kraft Paper Release Liner

### Benefits

- Highly elastic and very tough
- Abrasion resistant
- Extra thick for stay-flat and dimensional stability
- Conformable for curves and irregular surfaces
- Transparent for easy inspection
- Repositionable and easy to apply
- Excellent high and low temperature performance
- Smooth clean release - easy to use
- Die cuttable

### Typical Test Values

|                                | Standard UOM  |       | Metric UOM    |      | Test Method |
|--------------------------------|---------------|-------|---------------|------|-------------|
| <b>Total Thickness</b>         | 9.4           | mils  | 0.239         | mm   | PSTC-133    |
| <b>Substrate Thickness</b>     | 7.0           | mils  | 0.178         | mm   | PSTC-133    |
| <b>Adhesion to Steel</b>       | 75            | oz/in | 8.21          | N/cm | ASTM D-3330 |
| <b>Tensile Strength</b>        | 70            | lb/in | 122.59        | N/cm | ASTM D-3759 |
| <b>Elongation</b>              | 600%          |       |               |      |             |
| <b>Abrasion/Wear Index</b>     | 0.98          |       |               |      | ASTM D-4060 |
| <b>Application Temperature</b> | 50 to 120 °F  |       | 10 to 49 °C   |      |             |
| <b>Operating Temperature</b>   | -45 to 250 °F |       | -43 to 121 °C |      |             |

Recommended Storage Conditions: 40-60% Humidity, 60 - 80 °F  
 Standard Shelf Life (at 25 °C): 12 months from shipment date

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.