


## Polyethylene Film Tape - Colors



<b>Backing:</b>	LDPE Film
<b>Adhesive:</b>	Rubber (R400)
<b>Liner:</b>	N/A
<b>Colors:</b>	White, Black, Red, Blue, Yellow, Green
<b>Specifications:</b>	N/A
<b>Size Options:</b>	Incremental widths 1/4" - 54" x 108ft

### Applications

- General purpose sealing
- Splicing and seaming
- Color coding and aisle marking
- Bondbreaker tape
- Temporary hold down
- Thermal insulation outerwrap
- Industrial fabricating applications
- Decorative markings & striping

### Features

- LDPE Film
- Rubber Adhesive

### Benefits

- Conformable for irregular surfaces
- Excellent moisture barrier properties
- Stands up to mechanical and chemical wear
- Adheres well to a wide variety of surfaces
- Excellent surface wettability
- Solvent and moisture resistant
- Low in halogens and leachable chlorides

### Typical Test Values

	Standard UOM		Metric UOM		Test Method
<b>Total Thickness</b>	5.5	mils	0.140	mm	PSTC-133
<b>Substrate Thickness</b>	4.5	mils	0.114	mm	PSTC-133
<b>Adhesion to Steel</b>	25	oz/in	2.74	N/cm	ASTM D-3330
<b>Tensile Strength</b>	11	lb/in	19.26	N/cm	ASTM D-3759
<b>Elongation</b>	400%				
<b>Application Temperature</b>	50 to 120 °F		10 to 49° C		
<b>Operating Temperature</b>	-40 to 190 °F		-40 to 88 °C		

Recommended Storage Conditions: 40-60% Humidity, 60 - 80 °F  
Standard Shelf Life (at 25 °C): 12 months from shipment date

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.