

POLYKEN®

600 SERIES SEAM TAPES



**A seam you
can trust.**

**Every seam is a
potential weak spot.**

Polyken™ 600 Series Seam Tapes
seal the gaps that let in water, air, and
headaches.

With aggressive acrylic adhesives
and jobsite-grade backings,
they effectively seal seams,
overlaps, and damaged areas
on housewraps, sheathing, foam
boards, vapor barriers and other
building materials.

Built for extreme weather, UV
exposure, and jobsite realities,
these tapes save time during install
and keep walls protected for the
long haul.

Field-tested brands.



One tape series. Three solutions. Any seam.



BETTER

629

Reliable acrylic stick for standard wraps & overlaps — housewraps, vapor barriers, and quick repairs.



BEST

639*

Weather-tough acrylic that installs & holds under sun and cold—for housewraps and sheathing.



BEST+

649*

Heavy-duty acrylic on PET for rigid boards; foam/OSB/plywood, vapor barriers, and roof underlayments.


PRODUCT INFORMATION

	629	639*	649*
Adhesive Type	Acrylic		
Backing Type	BOPP	BOPP	PET
Adhesive Thickness	1.6 mils	2.0 mils	2.2 mils
Backing Thickness	1.6 mils	1.6 mils	1.4 mils
Tensile Strength	32 lb/in (56.04 N/cm)		High tensile / stable
Application Temp	-5 to 180°F (-20 to 82°C)		
Operating Temp	-30 to 200°F (-34 to 93°C)		
UV Resistance	6 months	1 year	1 year+
Colors	White, Red, Clear		
Sizes	48mm, 72mm widths		

*Available for private label opportunities only.


What we're made of.

Engineered backings, adhesives, and liners.



Acrylic Adhesive

Clean, pressure-activated adhesive. Long-term, UV resistant, and watertight—when paired w/ film.



Durable Backing (BOPP or PET)

Installs quickly and conforms to curves and edges, resists tearing

POLYKEN®

A field-tested brand from Vybond • vybond.com • 1204_9-25

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND's knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.