

Polyken **767UV** (7 mil) and **769UV** (9 mil) UV-Resistant PE Film Tapes offer excellent durability and moisture/solvent resistance along with high strength and conformability. The high tack, high adhesion synthetic rubber forms strong, clean removal bonds to a variety of surfaces for up to 28 days!



- Outdoor stucco, paint, and plaster mask • Protection around window and door frames
- Seam and patch shrink wrap material for equipment storage
- Agricultural bagging and bundling • Greenhouse repair
- Outdoor label and color coding • Outdoor wire hold down
- Temporary outdoor surface protection • Seaming and patching tarps and sheeting

Property	Polyken 767UV	Polyken 769UV
Thickness	7 mils	9 mils
Adhesion to Steel	75 oz/in	85 oz/in
Adhesion to Backing	35 oz/in	39 oz/in
Tensile Strength	25 lb/in	32 lb/in
Elongation	85%	70%
Permeance	0.11 US Perms	0.10 US Perms
Application Temperature Range	30 to 160 °F	30 to 160 °F
Operating Temperature Range	20 to 200 °F	20 to 200 °F

Contact your sales representative today for samples!

Re-Order Number	Color	Size/Edge	Rolls/Case	Cases/Pallet
Polyken 767UV				
1465176	Red	48mm x 55m Pinked	24	27
1467718	Red	48mm x 55m Straight	24	27
1465177	Red	96mm x 55m Pinked	12	27
1469761	Red	96mm x 55m Straight	12	27
1465178	White	48mm x 55m Pinked	24	27
1469762	White	48mm x 55m Straight	24	27
1465179	White	96mm x 55m Pinked	12	27
1469763	White	96mm x 55m Straight	12	27
Polyken 769UV				
1605851	Red	48mm x 55m Pinked	24	27
1605852	Red	48mm x 55m Straight	24	27
1605859	Red	96mm x 55m Pinked	12	27
1605860	Red	96mm x 55m Straight	12	27
1605855	Red	72mm x 55m Pinked	16	27
1605856	Red	72mm x 55m Straight	16	27
1603086	White	48mm x 55m Pinked	24	27
1605850	White	48mm x 55m Straight	24	27
1605857	White	96mm x 55m Pinked	12	27
1605858	White	96mm x 55m Straight	12	27
1605853	White	72mm x 55m Pinked	16	27
1605854	White	72mm x 55m Straight	16	27

Contact your sales representative today for samples!

