

ADCHEM

THE BEST BOND FOR MARINE DECKING



Pressure Sensitive Adhesive (PSA) tapes provide an instant, clean bond when pressure is applied—eliminating the need for flammable solvents, cure time, or messy liquid adhesives. In **marine flooring and decking applications**, PSA tapes offer a one-step solution that simplifies installation while delivering reliable performance in demanding environments.



Designed to withstand extreme temperatures, UV exposure, and moisture, PSA tapes work effectively with composite and wooden boat platforms.

Adchem® 650 Series Tapes are engineered to support efficient, professional installs with no mess adhesion, minimal waste, and the ability to reposition materials briefly for precise alignment before final bonding.

Field-tested brands.



650 SERIES

High-performance pressure-sensitive tapes perfect for marine flooring and decking applications. This series offers a variety of products delivering consistent bonds with a cleaner, faster install than traditional liquid adhesives to fit your job.

PRODUCT OFFERINGS

PRODUCT	ADHESIVE	CONSTRUCTION
652	Acrylic	Transfer
653		Transfer
654M		Double-Coated PET
654T		Double-Coated Tissue
654U		Transfer
655		Transfer



MADE IN THE USA

CONTACT A SALES REP TODAY!

BENEFITS

Clean, Fast Installation

- No flammable solvents
- No cure time — instant bond
- No dripping, spreading, or cleanup
- No adhesive bleed-through fabrics or decking materials

One-Step Bonding Solution

- Single product to purchase and install
- No extra supplies (no drop cloths, brushes, or masking tape)
- No hazardous waste or empty cans to dispose of

Marine-Ready Performance

- Withstands high and low temperatures
- Resistant to UV exposure and moisture
- Built for demanding marine environments
- Light-weight compared to mechanical fasteners or messy liquid adhesives

Material Compatibility

- Works with composite decking systems
- Compatible with wood-based boat platforms

Installer-Friendly

- Repositionable within the first few minutes for precise placement
- Apply pressure to achieve a strong, permanent bond
- A simple and quick peel-and-stick installation



2320 Bowling Green Rd., Franklin, KY 42134 • 1-800-343-7875 • Fax 1-800-328-4822 • vybond.com • 1219C_1-26

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND's knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.